







Mfg. & Exporter: General & Specialty Oilfield Chemicals Water Treatment Chemicals & Other Industrial Chemicals

Admin Office: 234, Ellis-Bridge Shopping Centre Opp. Town Hall, Ellis-Bridge, Ahmedabad - 380 006, Gujarat, India. Phone: +91 79 - 40069490 Tele-fax: +91 79 26575119 Cell: +91 98251 51308, 98254 74094 Email: info@sment.in Website: www.oilfieldchemicals.co.in / www.oilfieldchemicals.biz Reg. Office: 28, Ellis-Bridge Shopping Centre Opp. Town Hall, Ellis-Bridge, Ahmedabad - 380 006, Gujarat, India.

# PRODUCT DATA SHEET ACID CORROSION INHIBITOR (SE-CI 1021)

## • PRODUCT DESCRIPTION:

**SE-Cl 1021** is a highly concentrated Inhibitor contains Active Synergistic blend of Organic Acid-Amine Salts in aqueous Alcohol Solvents system.

#### • APPLICATION:

**SE-CI 1021** provides excellent protection from Corrosion to Oil Well Equipments, pumps and Trucks during Acid Job for Well Stimulation. Hydrochloric Acid of any strength has characteristic of reaction on metal. Acid Jobs carried-out in Oil Wells to remove Incrustation in the wells that stimulate the Oil/Gas Flows.

**SE-CI 1021** is highly concentrated Acid Inhibitor which provides excellent performance at high Temperature and Pressure, which protects damage of Well Equipments, Pumps and Trucks by Hydrochloric Acid during Acid Jobs for Well Stimulation.

Dose: From the field experience, standard range of Dose Rates is 20 to 40 ml/ltr.

#### • PHYSICAL PROPERTIES:

Appearance	Pale Yellow to Brown Color Homogeneous Liquid
рН	2.0 – 5.0
Viscosity	< 100 CPS @ 25° C
Density	0.95 ± 0.05 gm/ml @ 25° C
Solubility	Dispersible in Water
Corrosion Performance Test	Corrosion without pitting: 0.024 g/cm² to 0.044 g/cm²
	Type of Steel: N-80
	Type of Acid: Hydrochloric Acid (15% w/w)
	Dose: 20 to 40 ml/ltr
	Test Temperature: 120° C to 150° C
	Test Pressure: 1000 psi
	Test Condition & Duration: Static/6 Hours

### • HANDLING:

**SE-CI 1021** shall be stored in closed containers away from direct sunlight at ambient temperature. During handling, direct contact with human body is to be avoided. Safety goggles and gloves are recommended for safe handling. The spillage can be handled with dry absorbent like sand, sawdust, etc. On ingestion / eye contact with the product, medical attention should be sought immediately.

#### • PACKING:

Factory: Plot. No. 9/A, Ashwamegh Industrial Estate, Opp. Water Tank, Changodar, Ahmedabad- 382213, Gujarat, India.

Phone: +91 2717-297929









Mfg. & Exporter: General & Specialty Oilfield Chemicals Water Treatment Chemicals & Other Industrial Chemicals

Admin Office: 234, Ellis-Bridge Shopping Centre Opp. Town Hall, Ellis-Bridge, Ahmedabad - 380 006, Gujarat, India.

Phone: +91 79 - 40069490 Tele-fax: +91 79 26575119 Cell: +91 98251 51308, 98254 74094

Email: info@sment.in Website: www.oilfieldchemicals.co.in / www.oilfieldchemicals.biz

Reg. Office: 28, Ellis-Bridge Shopping Centre Opp. Town Hall, Ellis-Bridge, Ahmedabad - 380 006, Gujarat, India.

**SE-CI 1021** is available in 200 Liter HM/HDPE Barrels or as per Customer's requirement.

Factory: Plot. No. 9/A, Ashwamegh Industrial Estate, Opp. Water Tank, Changodar, Ahmedabad- 382213, Gujarat, India.

Phone: +91 2717-297929