



Admin Office: 234, Ellis-Bridge Shopping Centre Opp. Town Hall, Ellis-Bridge, Ahmedabad - 380 006, Gujarat, India.
Phone: +91 79 - 40069490 **Tele-fax:** +91 79 26575119 **Cell:** +91 98251 51308, 98254 74094
Email: info@sment.in **Website:** www.oilfieldchemicals.co.in / www.oilfieldchemicals.biz
Reg. Office: 28, Ellis-Bridge Shopping Centre Opp. Town Hall, Ellis-Bridge, Ahmedabad - 380 006, Gujarat, India.

PRODUCT DATA SHEET

OXYGEN SCAVENGER (SE-OSC 4752)

- PRODUCT DESCRIPTION:**

SE-OSC 4752 is a highly active, Liquid Oxygen Scavenger.

- APPLICATION:**

SE-OSC 4752 controls Corrosion caused due to Oxygen (O₂). **SE-OSC 4752** is a non-flammable liquid and completely soluble in Water. **SE-OSC 4752** controls Oxygen Corrosion of Tubular goods in drilling and completion fluids as well as in Oil Production Systems. **SE-OSC 4752** can be added directly to the Mud Pump suction Line with a Chemical Pump or added to the Mud Pit near the Pump suction.

Dose: Dose Rate **SE-OSC 4752** may vary with Application and amount of dissolved Oxygen present in the System.

- PHYSICAL PROPERTIES:**

Appearance	Yellow to Pink Colour Homogeneous Liquid
pH	3.0 – 5.0
Viscosity	< 50 CPS @ 25° C
Density	1.25 ± 0.10 gm/ml @ 25° C
Solubility	Soluble in Water

- HANDLING:**

SE-OSC 4752 shall be stored in closed containers away from direct sunlight at ambient temperature. During handling, direct contact with human body is to be avoided. Safety goggles and gloves are recommended for safe handling. The spillage can be handled with dry absorbent like sand, sawdust, etc. On ingestion / eye contact with the product, medical attention should be sought immediately.

- PACKING:**

SE-OSC 4752 is available in 200 Liter HM/HDPE Barrels or as per Customer's requirement.